

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 05/24/2022

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.
Product code : TM3554

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Synthetic Oil Treatment

1.3. Details of the supplier of the safety data sheet

Rev Your Cause LLC
1440 Jason Way
Unit 100-107
Santa Maria, CA 93455
T 805-925-2796

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS US classification

Carcinogenicity Category 1B H350 May cause cancer
Aspiration hazard Category 1 H304 May be fatal if swallowed and enters airways

Full text of H- and EUH-statements: see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H304 - May be fatal if swallowed and enters airways
H350 - May cause cancer

Precautionary statements (GHS US) :

P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,
P308+P313 - If exposed or concerned: Get medical advice/attention.
P331 - Do NOT induce vomiting.
P405 - Store locked up.
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	(CAS-No.) 64742-54-7	≥ 95	Not classified
Diisodecyl Adipate	(CAS-No.) 27178-16-1	1 – 5	Not classified

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
ALKYL DITHIOPHOSPHATE	(CAS-No.) Proprietary	0.396 – 0.66	Not classified
White Mineral Oil (Petroleum)	(CAS-No.) 8042-47-5	0.3 – 0.6	Asp. Tox. 1, H304
Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based	(CAS-No.) 72623-86-0	0.3 – 0.6	Carc. 1B, H350
Paraffinum Liquidum	(CAS-No.) 8012-95-1	0.3 – 0.6	Not classified
Distillates (Petroleum), Solvent Refined Heavy Paraffinic	(CAS-No.) 64741-88-4	0.3 – 0.6	Acute Tox. 4 (Oral), H302
Distillates (Petroleum), Solvent-Dewaxed Heavy Paraffinic	(CAS-No.) 64742-65-0	72-90	Not classified
	(CAS-No.) 64741-89-5	0.01 – 0.05	Carc. 1B, H350
3a,4,7,7a-tetrahydro-4,7-methanoindene	(CAS-No.) 77-73-6	0.007 – 0.032	Not classified

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : If you feel unwell, seek medical advice.
- Symptoms/effects after inhalation : May cause irritation or asthma-like symptoms.
- Symptoms/effects after skin contact : May cause slight irritation . Itching. Red skin.
- Symptoms/effects after eye contact : May cause slight eye irritation . Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
- Symptoms/effects after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released product, collect/pump into suitable containers. Plug the leak, cut off the supply.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Wash affected areas thoroughly after handling. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.	
No additional information available	
(64741-89-5)	
No additional information available	
Distillates (Petroleum), Solvent-Dewaxed Heavy Paraffinic (64742-65-0)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m ³ MIST 8 HOURS
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	5 mg/m ³ MIST 8 HOURS
White Mineral Oil (Petroleum) (8042-47-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m ³ (Inhalable fraction)
ACGIH OEL STEL	10 mg/m ³
Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)	
No additional information available	
Paraffinum Liquidum (8012-95-1)	
No additional information available	
Distillates (Petroleum), Solvent Refined Heavy Paraffinic (64741-88-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m ³
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	5 mg/m ³ Oil Mist Limit
3a,4,7,7a-tetrahydro-4,7-methanoindene (77-73-6)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	5 ppm (Dicyclopentadiene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH OEL STEL [ppm]	1 ppm
ALKYL DITHIOPHOSPHATE (Proprietary)	
No additional information available	
Diisodecyl Adipate (27178-16-1)	
No additional information available	
Distillates (Petroleum), Hydrotreated Heavy Paraffinic (64742-54-7)	
No additional information available	

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Milky.
Odor	: Mild . Petroleum-like odour.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 100 °C
Flash point	: > 150 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: > 1
Relative density	: 0.83
Solubility	: Insoluble in water. Water: Negligible
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 7.3 – 19.6 cSt @ 40 deg C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

VOC content : < 1 %

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

White Mineral Oil (Petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg (Rat; Experimental value,Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Experimental value,Rabbit; Experimental value)
LC50 Inhalation - Rat	> 5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol), 14 day(s))

Distillates (Petroleum), Solvent Refined Heavy Paraffinic (64741-88-4)	
LD50 oral rat	≈ 1120 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
ATE US (oral)	500 mg/kg body weight

3a,4,7,7a-tetrahydro-4,7-methanoindene (77-73-6)	
LD50 oral rat	590 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, 75 % aqueous solution, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat	1.723 mg/l air (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer.
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : May be fatal if swallowed and enters airways.
Viscosity, kinematic : 7.3 – 19.6 mm²/s @ 40 deg C
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
Symptoms/effects : If you feel unwell, seek medical advice.
Symptoms/effects after inhalation : May cause irritation or asthma-like symptoms.
Symptoms/effects after skin contact : May cause slight irritation . Itching. Red skin.
Symptoms/effects after eye contact : May cause slight eye irritation . Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/effects after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

White Mineral Oil (Petroleum) (8042-47-5)	
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
3a,4,7,7a-tetrahydro-4,7-methanoindene (77-73-6)	
LC50 - Fish [1]	15.9 mg/l (US EPA, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	0.823 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	0.574 mg/l Test organisms (species): Daphnia sp. Duration: '21 d'
NOEC chronic fish	0.98 mg/l Test organisms (species): Lepomis macrochirus Duration: '14 d'

12.2. Persistence and degradability

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.	
Persistence and degradability	Not established.
(64741-89-5)	
Persistence and degradability	Not established.
Distillates (Petroleum), Solvent-Dewaxed Heavy Paraffinic (64742-65-0)	
Persistence and degradability	Biodegradability in water: no data available. Not established.
White Mineral Oil (Petroleum) (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water. Adsorbs into the soil. Not established.
Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)	
Persistence and degradability	Not established.
Paraffinum Liquidum (8012-95-1)	
Persistence and degradability	Not established.
Distillates (Petroleum), Solvent Refined Heavy Paraffinic (64741-88-4)	
Persistence and degradability	Not established.
3a,4,7,7a-tetrahydro-4,7-methanoindene (77-73-6)	
Persistence and degradability	Not established.
ThOD	3.15 g O ₂ /g substance
ALKYL DITHIOPHOSPHATE (Proprietary)	
Persistence and degradability	Not established.
Diisodecyl Adipate (27178-16-1)	
Persistence and degradability	Readily biodegradable in water.
Distillates (Petroleum), Hydrotreated Heavy Paraffinic (64742-54-7)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.	
Bioaccumulative potential	Not established.
(64741-89-5)	
Bioaccumulative potential	Not established.
Distillates (Petroleum), Solvent-Dewaxed Heavy Paraffinic (64742-65-0)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 (Calculated)
Bioaccumulative potential	No bioaccumulation data available. Not established.
White Mineral Oil (Petroleum) (8042-47-5)	
BCF - Other aquatic organisms [1]	1216 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.18 (Experimental value)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5). Not established.
Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)	
Bioaccumulative potential	Not established.
Paraffinum Liquidum (8012-95-1)	
Bioaccumulative potential	Not established.
Distillates (Petroleum), Solvent Refined Heavy Paraffinic (64741-88-4)	
Bioaccumulative potential	Not established.

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3a,4,7,7a-tetrahydro-4,7-methanoindene (77-73-6)	
BCF - Fish [1]	53 (Equivalent or similar to OECD 305, 14 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	2.78 (Experimental value, 25 °C)
Bioaccumulative potential	Not established.

ALKYL DITHIOPHOSPHATE (Proprietary)	
Bioaccumulative potential	Not established.

Diisodecyl Adipate (27178-16-1)	
BCF - Fish [1]	34.4 – 316 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	9.56 – 10.4 (Practical experience/observation, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Distillates (Petroleum), Hydrotreated Heavy Paraffinic (64742-54-7)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

White Mineral Oil (Petroleum) (8042-47-5)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Koc)	2.64 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

3a,4,7,7a-tetrahydro-4,7-methanoindene (77-73-6)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Koc)	3.18 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for mobility in soil. Not toxic to bees.

Diisodecyl Adipate (27178-16-1)	
Partition coefficient n-octanol/water (Log Koc)	5.827 – 6.992 (log Koc, Calculated value)
Ecology - soil	Adsorbs into the soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Proper Shipping Name (DOT) : Not Regulated

Other information : No supplementary information available.

Transport by sea

Air transport

Proper Shipping Name (IATA) : Not Regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates (Petroleum), Solvent-Dewaxed Heavy Paraffinic (64742-65-0)

SARA Section 311/312 Hazard Classes Delayed (chronic) health hazard

White Mineral Oil (Petroleum) (8042-47-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Paraffinum Liquidum (8012-95-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates (Petroleum), Solvent Refined Heavy Paraffinic (64741-88-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Diisodecyl Adipate (27178-16-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates (Petroleum), Hydrotreated Heavy Paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

White Mineral Oil (Petroleum) (8042-47-5)

Listed on the Canadian DSL (Domestic Substances List)

Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)

Listed on the Canadian DSL (Domestic Substances List)

Paraffinum Liquidum (8012-95-1)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (Petroleum), Solvent Refined Heavy Paraffinic (64741-88-4)

Listed on the Canadian DSL (Domestic Substances List)

Diisodecyl Adipate (27178-16-1)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (Petroleum), Hydrotreated Heavy Paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)

Paraffinum Liquidum (8012-95-1)

Distillates (Petroleum), Solvent Refined Heavy Paraffinic (64741-88-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Diisodecyl Adipate (27178-16-1)

Distillates (Petroleum), Hydrotreated Heavy Paraffinic (64742-54-7)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)

Paraffinum Liquidum (8012-95-1)

Distillates (Petroleum), Solvent Refined Heavy Paraffinic (64741-88-4)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Diisodecyl Adipate (27178-16-1)

Distillates (Petroleum), Hydrotreated Heavy Paraffinic (64742-54-7)

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.()	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - California - Proposition 65

(64741-89-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Distillates (Petroleum), Solvent-Dewaxed Heavy Paraffinic (64742-65-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

White Mineral Oil (Petroleum) (8042-47-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Paraffinum Liquidum (8012-95-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Distillates (Petroleum), Solvent Refined Heavy Paraffinic (64741-88-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

(77-73-6)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

ALKYL DITHIOPHOSPHATE (Proprietary)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

THROTTLE MUSCLE SYNTHETIC ENGINE ARMOR 16 FL. OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Diisodecyl Adipate (27178-16-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Distillates (Petroleum), Hydrotreated Heavy Paraffinic (64742-54-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Paraffinum Liquidum (8012-95-1)				
State or local regulations				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List				

Distillates (Petroleum), Solvent Refined Heavy Paraffinic (64741-88-4)				
State or local regulations				
New Jersey Right-to-Know U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				

SECTION 16: Other information

Indication of changes : Revision - See : *

Other information : None.


Full text of H-phrases:

H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H350	May cause cancer

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

Personal protection : B

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.